

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number
WO 2005/092139 A1

(51) International Patent Classification⁷: **A44B 19/42,**
B65D 33/25

(21) International Application Number:
PCT/GB2005/001078

(22) International Filing Date: 22 March 2005 (22.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0406626.2 24 March 2004 (24.03.2004) GB

(71) Applicant (for all designated States except US):
SUPREME PLASTICS HOLDINGS LIMITED
[GB/GB]; Supreme House, 300 Regents Park Road,
Finchley, London N3 2TL (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LEIGHTON, Mur-**
ray, Edward, Bruce [GB/GB]; 19 Victoria Avenue,
Whitby Bay, Tyne and Wear NE26 2BA (GB).

(74) Agent: **ACKROYD, Robert**; W.P. Thompson & Co.,
Eastcheap House, Central Approach, Letchworth Garden
City, Hertfordshire SG6 3DS (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

[Continued on next page]

(54) Title: APPLICATION OF ZIPPER LENGTHS TO A WEB



(57) Abstract: The apparatus comprises a rotary turret (18) having circumferentially spaced grooves (30a, 30b, 30c) for receiving pre-cut lengths of zipper (58) consisting of first and second interengageable profile strips. Sliders (46) for engaging and re-engaging the profiles are mounted on the zipper lengths by a rotary slider applicator (42). A web (12) of plastics material is fed beneath the turret (18) and receives the zipper lengths which are secured to the web by a heated sealing bar (60). The web with zippers attached is fed to a form-fill-seal machine (20) on which the web is formed into individual bags which are filled and separated from one another.

WO 2005/092139 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.